

THE UNIVERSAL CLOSERS FOR STANDARD DOORS – TESTED AND APPROVED TO EN 1154

As units designed especially for interior applications, the TS 92 and TS 91 door closers constitute the perfect complement to the DORMA TS 93 cam-action door closer system. They likewise come in the Contur design and, thanks to their linear drive mechanism with heart-shaped cam, they offer the same ease of use. Moreover, their competitive pricing combined with their outstanding level of assured quality make them particularly attractive from an economic standpoint as well.

Certified to ISO 9001

Data and features		TS 92 B/G ¹⁾	TS 91 B
Closing force	Size	EN 1-4	EN 3
Adjustable		•	-
Standard doors ²⁾	≤ 950 mm	_	•
	≤ 1100 mm	•	-
External doors, outward opening ²⁾		_	-
For fire and smoke check doors		•	•
Non-handed design		•	•
Arm assembly type	Slide channel	•	•
Closing speed and latching			
action independently	180°-15°	•	•
adjustable at two		•	•
separate valves	15°- 0°		
Cushioned limit stay, mechanical		0	0
Backcheck		-	-
Delayed action		-	-
Hold-open		0	0
Weight in kg		2.0	1.9
Dimensions in mm	Length	281	267
	Overall depth	47	47
	Height	65	65
Door closer tested to EN 1154	1	•	•
CE mark for building products		٠	•

● yes - no ○ optional

 $^{1)}$ B = Standard model for pull-side door leaf fixing/push-side transom fixing

G = Special model for push-side door leaf fixing/pull-side transom fixing.

²⁾ For particularly heavy doors and doors which have to close against wind resistance, we recommend the DORMA TS 93.

certifire

The TS 92/TS 91 complies with the requirements and/or recommendations of the following: CERTIFIRE approved for fire doors ITT 120, MM/IMM 240; Ref. CF 119





Plus points

For the trade

- Inexpensive cam-action technology for standard interior doors.
- Low storage costs and reduced inventory requirement thanks to uniform slide channels of the Contur series.

For the fabricator

- Non-handed.
- Easy to fix and quickly adjustable.

For the architect/specifier

- Excellent value for money.Uniform appearance
- throughout the entire Contur slide channel range.

For the user

- Exceptional ease of use and fully controlled closing action.
- Optimum adaptability of the closing speed with reliable latching thanks to two regulating valves.