# Rim Locks - Standard Security

#### 1158 / L1158

## **Cylinder Roller Bolt Deadlock**



#### **Application:**

- For timber doors from 35-60mm thick, hinged on the left or right and opening inwards only
- Concealed fixing
- Not recommended for glass panelled doors
- Also suitable for steel and composite doors special fixings required







### **Specification:**

- The roller bolt operates with a simple push/pull action
- The roller bolt may be locked or withdrawn by key outside and handle inside
- Backset: 60mmCase & Keep: Zinc
- · Roller Bolt: Anodised Brass finish with nylon roller
- Handle: Zinc, finished to match case and keep material
- Outside Cylinder: Brass, 5 pin tumbler mechanism
- Inside Cylinder: n/a
- Keying Groups: May be supplied to pass, differ & master keyed. Supplied with 2 steel nickel plated keys as standard
- Master keyed products supplied with nickel silver keys
- Key Blank Number: KB8-NP
- Available Boxed or Visi Packed
- For an alternative to this product which assists in fulfilling the duties required under the Equality Act please see 1158EA / L1158EA
- · Case only: Available in CG, EB, WE and CH finishes
- Case & Cylinder: Available in CG-PL, EB-PL, CG-SC, SC-SC, WE-PL, WE-SC, CH-CH and DMG-CH finishes



