

Rim Locks - Security

1038 / L1038

Standard Stile Cylinder Night Latch



ASSA ABLOY

Application:

- For timber doors from 35-60mm thick, hinged on the left or right and opening inwards only
- Suitable for glass panelled doors
- Not recommended for single door entry residencies
- Concealed fixing
- Also suitable for steel and composite doors - special fixings required



Specification:

- The bolt is withdrawn by key outside and handle inside
- The bolt may be held in the locked or in the withdrawn position by operating the snib
- When the door is closed the bolt is automatically locked against end pressure by the anti-thrust slide
- Turning key a full revolution anti-clockwise deadlocks handle
- Backset: 60mm
- Case & Keep: Zinc
- Latch Bolt: Anodised Brass finish
- Handle: Zinc, finished to match case and keep material
- Outside Cylinder: Brass, 5 pin tumbler mechanism
- Inside Cylinder: n/a
- Keying Groups: May be supplied to pass, differ & master keyed. Supplied with 2 steel nickel plated keys as standard
- Master keyed products supplied with nickel silver keys
- Key Blank Number: KB8-NP
- Variant: 10381 - non-deadlocking, ideal for use in hotels and institutions. The snib retains bolt in withdrawn position. Only supplied complete with cylinder
- Available Boxed or Visi Packed
- Case only: Available in CG, EB, WE, SC and DMG finishes
- Case & Cylinder: Available in CG-PL, EB-PL, SC-SC, WE-PL, WE-SC and CH-CH finishes

