




INFO

Select the detailed dimensional drawing of the multipoint locking using the locking pattern → *from page 308.*

3.2.2.2 3 bolts (3CB) – couplable



16

											
2230 – 3000	35	92	8	1020	KO	–	–	C600	Roto Sil	5 Piece(s)	782959
	45	92	8	1020	KO	–	–	C600	Roto Sil	5 Piece(s)	776558
	55	92	8	1020	KO	–	–	C600	Roto Sil	5 Piece(s)	776566
	65	92	10	1020	KO	–	–	C600	Roto Sil	5 Piece(s)	776573



20

											
2230 – 3000	65	92	10	1020	KO	–	–	C600	Roto Sil	5 Piece(s)	780202



INFO

Select the detailed dimensional drawing of the multipoint locking using the locking pattern → *from page 308.*

Connector components



								
2230 – 2700	600	F16	300	–	Bolt	Roto Sil	5 Piece(s)	620682
		F20	300	–	Bolt	Roto Sil	5 Piece(s)	620689
2700 – 3000	900	F16	300	–	Bolt	Roto Sil	5 Piece(s)	620685
		F20	300	–	Bolt	Roto Sil	5 Piece(s)	620692



INFO

Connector components 600

SRH 2230 – 2530 mm: the coupling point on the multipoint locking must be cropped by 170 mm.

SRH 2400 – 2700 mm: do not crop the coupling point on the multipoint locking.