

# Rim Locks - Standard Security

## 1026 / L1026


### Narrow Stile Cylinder Night Latch



#### Technical Design:

#### Application:

- For timber doors from 35-60mm thick, hinged on the left or right and opening inwards only
- Concealed fixing
- Not recommended for glass panelled doors
- Also suitable for steel and composite doors - special fixings required



#### Specification:

- The bolt is withdrawn by key outside and handle inside
- The bolt may be held in the locked or in the withdrawn position by operating the snib
- Backset: 50mm
- Case & Keep: Zinc
- Latch Bolt: Anodised Brass finish
- Handle: Zinc, finished to match case and keep material
- Outside Cylinder: Brass, 5 pin tumbler mechanism
- Inside Cylinder: n/a
- Keying Groups: May be supplied to pass, differ & master keyed. Supplied with 2 steel nickel plated keys as standard.
- Master keyed products supplied with nickel silver keys
- Key Blank Number: KB8-NP
- For an alternative to this product which assists in fulfilling the duties required under the Equality Act please see 1026EA / L1026EA
- Available Boxed or Visi Packed
- Case only: Available in CG, EB, SC, WE and DMG finishes
- Case & Cylinder: Available in CG-PL, EB-PL, WE-PL, WE-SC, CH-CH and DMG-CH finishes

