




Technical features:

- Carbonitrided solid steel body, with chemical anti-corrosion nickel-plating treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- **The removable cylinder can be either rekeyed or replaced**
- Carbonitrided steel plug protection plate
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- LIM patented key profile

Supplied as standard:

- 2 keys

Type	Description						Key item	Unit weight	Pieces	ITEM			
		A	C	D	L	S				Pins	Type	Dim.	Hand




66	20,0	10,0	11,0	25,0	5	1 00401 00 1	0,685	6	1 28550 66 0
66	18,0	14,0	17,5	28,0	5	1 00401 00 1	0,837	6	1 28550 67 0
75	27,0	12,0	13,5	28,0	5	1 00401 00 1	0,852	6	1 28550 75 0
84	36,0	12,0	17,5	28,0	5	1 00401 00 1	0,970	6	1 28550 84 0
84	36,0	14,0	17,5	28,0	5	1 00401 00 1	0,983	6	1 28550 85 0

Type	Description	Key item					Unit weight	Pieces	ITEM				
		A	C	D	L	S			Plns	Type	Dim.	Hand	Fin.



• Clam packing

62	25,0	11,0	25,0	25,0	5	1 00401 00 1	0,768	6	1	28355	62	0
73	31,0	14,0	28,0	28,0	5	1 00401 00 1	1,140	6	1	28355	73	0



66	20,0	10,0	11,0	25,0	5	1 00401 00 1	0,685	6	1	28550	66	0
66	18,0	14,0	17,5	28,0	5	1 00401 00 1	0,837	6	1	28550	67	0
75	27,0	12,0	13,5	28,0	5	1 00401 00 1	0,852	6	1	28550	75	0
84	36,0	12,0	17,5	28,0	5	1 00401 00 1	0,970	6	1	28550	84	0
84	36,0	14,0	17,5	28,0	5	1 00401 00 1	0,983	6	1	28550	85	0



• Clam packing

66	20,0	10,0	11,0	25,0	5	1 00401 00 1	0,745	6	1	28555	66	0
66	18,0	14,0	17,5	28,0	5	1 00401 00 1	0,855	6	1	28555	67	0
75	27,0	12,0	13,5	28,0	5	1 00401 00 1	0,905	6	1	28555	75	0
84	36,0	12,0	17,5	28,0	5	1 00401 00 1	1,018	6	1	28555	84	0
84	36,0	14,0	17,5	28,0	5	1 00401 00 1	1,009	6	1	28555	85	0